



# MATERIAL SAFETY DATA SHEET

Last Update: October 14, 2009

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Emergency Contact: CHEMTREC **800-424-9300**

ANSI 2400.1 Format

Product Name: GreatSeal Gutter Sealant  
Item Number: GS-100  
Chemical Name: Silyl Terminated Polyether sealant  
Comparable Products: GreatSeal PE-150  
Product Use: Moisture cure sealant  
Company Information: STS Coatings, Inc.  
347 Hwy 289  
Comfort, TX 78013 USA  
Ph. 830-995-5177 Fax 830-995-5705

Prepared by: Cayce Kovacs

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS NO.	CONCENTRATION
Amino Silane	1760-24-3	proprietary

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW:

HMIG	
Health	1
Flammability	0
Reactivity	0
Protective Equipment	B

### HUMAN EFFECTS AND SYMPTOMS OF EXPOSURE:

ROUTES OF ENTRY: Dermal contact, Eye  
ACUTE EYE CONTACT: direct contact can cause severe irritation.  
ACUTE SKIN CONTACT: direct contact can cause slight irritation.  
SKIN ABSORPTION: Not toxic  
ACUTE INHALATION: Product is extremely low in volatility and therefore not likely to pose a problem from inhalation.  
ACUTE INGESTION: May be harmful if ingested, not a likely route of entry.  
CHRONIC EXPOSURE: Repeated or prolonged direct contact to the eyes may cause chemical burns. Repeated or prolonged direct contact to the skin may cause a dermatitis.  
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting skin and eye disorders may be aggravated by direct contact to this product.  
CARCINOGENICITY: There are no components in this product that are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

## 4. FIRST AID MEASURES

FIRST AID FOR EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. Get medical attention if ill effects or irritation occurs.  
FIRST AID FOR SKIN: Clean product from affected area with Ethyl alcohol, then wash with soap and water.  
FIRST AID FOR INHALATION: An unlikely route of entry. If affected, remove individual to fresh air. Consult a physician.  
FIRST AID FOR INGESTION: An unlikely route of entry. Consult a physician.

## 5. FIRE FIGHTING MEASURES

SPECIAL FIREFIGHTING PROCEDURES: None. As in any fire, wear self-contained breathing apparatus and full protective gear.

<sup>1</sup> Hazard Ratings: least = 0 slight = 1 moderate = 2 high = 3 extreme = 4 Based upon NPCA guidelines



EXTINGUISHING MEDIA: Water, CO<sub>2</sub>, dry chemical, foam.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: None. This product is not considered flammable.  
FLASH POINT: not applicable  
UPPER FLAMMABLE LIMIT: not applicable  
LOWER FLAMMABLE LIMIT: not applicable  
AUTOIGNITION TEMPERATURE: not applicable  
SENSITIVITY TO IMPACT: not applicable  
SENSITIVITY TO STATIC DISCHARGE: not applicable  
HAZARDOUS COMBUSTION PRODUCTS: Thermal decomposition may produce toxic fumes of carbon monoxide and/or carbon dioxide.

#### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protection recommended in section 8.  
METHODS FOR CLEANING UP: Collect spill with absorbent material such as cardboard and place into a container approved for waste disposal.

#### 7. HANDLING AND STORAGE

HANDLING: Use personal protection recommended in section 8. Avoid eye, skin and clothing direct contact.  
STORAGE: Keep container tightly closed in a dry, cool and well-ventilated place. This product polymerizes when in contact with moisture.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: No established limits.  
ENGINEERING CONTROLS: No specific controls are needed.  
PERSONAL PROTECTIVE EQUIPMENT:  
EYE PROTECTION: Use safety glasses or goggles to avoid direct eye contact.  
SKIN PROTECTION: Wear protective gloves such as vinyl to minimize contact with skin.  
RESPIRATORY PROTECTION: Respiratory protection is not required for this product.  
WORK/HYGIENIC PRACTICES: Avoid contact with eyes and skin. Wash thoroughly after handling and before eating or drinking.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: paste (reacts with moisture to become a firm synthetic rubber)  
SPECIFIC GRAVITY: varies from color to color. All colors are heavier than water.  
ODOR AND APPEARANCE: mild ester odor, paste, blue color  
BULK DENSITY: 11.9 lbs/gallon  
EVAPORATION RATE: not applicable  
BOILING POINT (F): not established  
FREEZE POINT: not established  
VAPOR DENSITY (air = 1): > 1  
VAPOR PRESSURE (mmHg): Not established  
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not established  
VISCOSITY: 30,000 cP

#### 10. STABILITY AND REACTIVITY

STABILITY: considered stable  
CONDITIONS TO AVOID: None known.  
INCOMPATIBLE MATERIALS: None known.  
REACTIVITY: Hazardous reaction will not occur.  
HAZARDOUS DECOMPOSITION PRODUCTS: None known.  
HAZARDOUS POLYMERIZATION: Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

Information below is based on Amino Silane (refer to sections 2 and 3 above)



ORAL: Result: LD50 > 2,000 mg/kg. Remark: Very low order of toxicity  
SKIN ABSORPTION RESULT: LD50 > 2,000 mg/kg. Remark: very low order of toxicity  
SKIN DIRECT CONTACT RESULT: slight irritation  
EYE DIRECT CONTACT RESULT: severe irritation. Remark: causes corneal injury  
INHALATION RESULT: LC50 not acutely toxic  
EXPOSURE LIMITS: not applicable  
SENSITIZATION: no  
REPRODUCTIVE TOXICITY: no  
MUTAGENICITY: no  
TERATOGENICITY: no  
SYNERGISTIC PRODUCTS: none

## 12. ECOTOXICOLOGICAL INFORMATION

No known applicable information.

## 13. DISPOSAL CONSIDERATIONS

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. This product becomes a firm synthetic rubber when cured. Please allow to cure before disposal.

## 14. TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION: none  
DOT: not regulated  
TDG: not available  
PIN: not available

## 15. REGULATORY INFORMATION

OSHA 29 CFR 1910-1200: Irritant

SARA Title III:

Section 302 – extremely hazardous substances: none  
Section 304 – not applicable  
Section 311/312 – immediate (acute) health hazard  
Section 313 - none

TSCA: All components of this product are listed on TSCA Inventory.

CERCLA REPORTABLE QUANTITY: not applicable

RCRA: Refer to section 13.

CA Proposition 65 Warning: This product contains no levels of listed substances which the State of California has found to cause cancer, birth defects, and/or other reproductive harm.

WHIMS CLASSIFICATION: D2B

## 16. OTHER INFORMATION

Prepared in accordance with 29 CFR 1910.1200

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The information and recommendations contained herein are to the best of STS Coatings, Inc. knowledge and belief, accurate and reliable as of the date issued. STS Coatings, Inc. Does not warrant or guarantee their



accuracy or reliability, and STS Coatings, Inc. shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the users responsibility to make certain that it is relying up on the most recent, updated, information and recommendations available from STS Coatings, Inc.

The Environmental Information included as well as the Hazardous Material Identification System (HMIS) and National Fire Protection Association (NFPA) ratings, have been included by STS Coatings, Inc. in order to provide additional health and hazard classification information. The ratings recommended are based up on the criteria supplied by the developers of these rating systems, together with STS Coatings, Inc.'s interpretation of the available data.

For Other Product Information Contact:  
STS Coatings, Inc.  
347 Hwy 289, Comfort, TX 78013  
PH. 830-995-5177  
FAX 830-995-5705  
info@stscoatings.com