



GreatSeal GS-100 Gutter Sealant

Product Description

GreatSeal GS-100 Gutter Sealant is a moisture curing, 100% solids, zero solvent, semi-self leveling seam and gutter sealant. It cures to a tough rubber seal when exposed to atmospheric moisture, withstanding joint movement due to weather and temperature changes. It will not crack or become brittle.

Basic Use

GreatSeal GS-100 Gutter Sealant is for use on seams, joints and cracks in gutters and downspouts. It can be painted 2 hours after application.

Limitations

Apply at temperatures between 30°F and 120°F. Do not prime substrates with asphalt primer.

Surface Preparation

All surfaces to be sealed must be clean and free of dirt, dust, oil, rust, water and ice before application. Clean any contaminated surfaces with alcohol. Do not use petroleum-based solvents for surface preparation.

Application

GreatSeal GS-100 is applied with any standard caulking gun. Cut plastic nozzle to size of desired bead and puncture inner seal.

Coverage

One 10 oz tube covers approximately:

1/8" bead: 97 lineal feet

1/4" bead: 30 lineal feet

Packaging

Tubes (10.1 oz), 24 tubes to carton

Carton: 24 lbs

Technical Data

Viscosity(Brookfield RTV)30,000 – 60,000 cps
Skin Over Time:30 minutes. @ 70°F 40% RH
Set time (60mil film, 70% RH):50% cure in 8 hour
.....75% cure in 24 hours
.....95% cure in 3 days
Elongation @ break 425% (7 day ambient cure)
Appearance:grayish, aluminum
Density:specific gravity = 1.4 (12.2 lbs / gallon)
ShrinkageNo measurable shrinkage (14 day cure)
Durometer:12 Shore A
Odor:mild mint ester
no odor once cured
VOCs:0%, zero
Solids:100%
Shelf Life:1 year

Technical Services

Technical advice on use of material for specific application and end use requirements is available from the manufacturer. Material Safety Data Sheet (MSDS) should be consulted for further information. This product is for industrial and professional use only.

Cautions

Uncured adhesive irritates eyes. In case of contact with eyes, immediately flush with water. Contact a physician. Avoid prolonged contact with skin.

FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

Warranty

This product is manufactured of good materials and by competent workmen. Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before installing, user shall determine the suitability of the product for his/her intended use; and user assumes all risk and liability.

STS Coatings, Inc.
347 Hwy 289, Comfort, TX 78013
(830)995-5177 phone (830)995-5705 fax
WWW.STSCOATINGS.COM
A Certified Texas HUB Manufacturer